

DL7200 SERIES FEATURES



操作空間大，方便縫製物移動

Working space is wide for moving sewing material.




安全開關，機器傾斜時即停機，確保安全

Safety switch : Stops running when the machine is tilted to ensure safety.



採用小型直驅伺服馬達，起縫快速，定位精準，低噪音，無皮帶屑污染

Mini direct drive servo motor system provides quick start sewing, precise positioning, low noise, and no belt dust.



耗能小，較皮帶驅動可節能35%

Low power consumption, it saves 35% energy against V-belt driving.



全自動供油確保機器在高速下的耐用性

Auto-lubrication ensures the mechanism's durability in high speed.



最大針距可達4針/英寸

Maximum stitch length is up to 4 stitch/ inch.



[選配] 不銹鋼車布導板

[Optional] Stainless steel sewing bed



圓刀式切線，棉線、絲光線均可輕易切斷

Rotary thread trimmer is applicable to various type of thread.




可調節亮度的LED燈

Adjustable LED light.



配備電子夾線器，補針按鍵安裝在倒縫按鍵的上方，方便工人操作






Equipped with electric thread nipper. Half-stitch key is set above the reverse key for easy using.



針送機構 (NM · NH) : 針送機構提供安定且強韌的送布力，針與布的不同步動作使線跡整齊，避免錯位的發生

Needle Feed Model(NM, NH): The needle-feeding mechanism provides stability and efficiency of feed, and prevents uneven material feed effectively.

規格/ SPECIFICATION

L3						功能選配 Function			
						代碼 Function Code	倒縫 Reverse Feeding	電子夾線 Thread Nipper	抬壓腳 Auto Lifter
DL7200-BH1	0-6	15.5	手動 Hand 5.5	自動 Auto 10-13	#20~#23	3500	V	V	V
DL7200-BM1	0-5	18			#11~#14	4000			
DL7200-BX2	0-7	18			#20~#23	3500			
DL7200-NM1	0-4	14.7			#11~#14	4000			
DL7200-NH1	0-5	14.7			#20~#23	3500			