


ASC-PBH100

Automatic Flat Bottom Hemming Machine

自動平下擺折縫機



SIRUBA



1. 降低人工縫製難度，無須技能工操作。
2. 站立式操作模式
3. 輸送帶傳送機構
4. 自動切邊裝置
5. 步進電機控制系統
6. 自動收料系統

- 1.Reducing the difficulty of manual sewing, and eliminating the need for skilled labor.
- 2.Stand-up operating mode.
- 3.Conveyor belt transmission mechanism.
- 4.Automatic edge-cutting device.
- 5.Stepper motor control system.
- 6.Automatic material receiving system.

特點

FEATURES

- 1 自動送料裝置，可連續穩定的自動送料。效率高、穩定性強。**
Automatic Feeding Device
 An automatic feeding device that enables continuous and stable automatic feeding. High efficiency and strong stability.
- 2 自動剪線頭裝置，用於切除布料多餘的線頭，適應惡劣環境能力強、穩定性和可靠性高。**
Automatic Thread Cutting Device
 Used to trim excess threads from fabric, with strong adaptability to harsh environments and high stability and reliability.
- 3 左修刀切布邊裝置，用於去掉布料毛邊，從而達到修整縫製，使成品更加美觀、質量更好。提高成品美觀度，大大提升成品價值。**
Left Hand Side Fabric Trimmer Device
 Used to remove fabric edges, achieving seam finishing for a more aesthetically pleasing and higher-quality finished product. Enhances the visual appeal of the finished product and significantly increases its value.



規格

SPECIFICATIONS

型號 Model	ASC-PBH100		
縫紉機機頭 Machine Head	SiRUBA C007L-W812A-356/CRL-/DCLH1-1		
車縫速度 Sewing Speed	3500 SPM (Max)		
車縫範圍 Sewing Range		折邊寬度 Hem Width	
氣壓 / 耗氣量 Air Pressure / Air Consumption	>0.4 Bar/ 190L	生產效率 Production Capacity	360~480 片 / 小時 360~480 PCS / Hour
電源電壓 Power Supply	220V	IOT 物聯對接 (選配) IOT interconnection	下單時，可依需求選擇加購 Please select it when ordering
機器尺寸 Dimensions	(W) 2300×(D) 610×(H) 1450 cm		