

ASP-SFS SERIES

自動縫線收尾加固縫機

Automatic suction
Bartacking and cutting of
Flatseam chain machine

影片連結
Video link



特點

FEATURES

1

對位凹槽方便操作員對位
Notch for alignment.

2

感測自動吸線，踏板啟動，壓腳、切線、自動套結車縫
Once the sensor detects the garment, the air suction will activate automatically and press the pedal to trim the flatseam chain and Bartacking Sensor.

3

小銅嘴(250mm)·作業員放布順手·容易操作
Small cylinder bed. Feed the garment with ease.

4

壓腳固定布面，滑動板送布設計，不傷布料，套結品質一致
Press the garment with presser foot and feed the garment with sliding plate to ensure the stable output.



規格

SPECIFICATIONS

型號 Model	ASP-SFS100A ASO-SFS100A	ASP-SFS100B ASO-SFS100B
縫紉機機頭 Machine Head	SiRUBA LKS-1900AN-FS	
車縫速度 Sewing Speed	2000 SPM (最高Max)	
使用針型 Needle Type	DP×5 #11	
車縫範圍 Sewing Range		
送布位置 Feeding Position	斜拉，壓腳位於中心右方 Pull oblique and presser foot is to the right of center	直拉，壓腳位於中心 Pull straight and presser foot is in the center
氣體消耗量 Air Consumption	175 L/min	
氣壓 Air Pressure	0.5 MPa	
電源電壓 Power Supply	Single Phase 1Φ AC200~240V 50/60 Hz	
消費電力 Power Consumption	100 W (Max)	
機器尺寸 Dimensions	(W)1200×(D)750×(H)1530 mm (With table and thread stand 含桌板、線架)	
生產效率 Production Capacity	車縫速度: 2000 SPM、車縫時間: 2.5秒/件、產速: 10秒/ 件 Sewing speed:2000 SPM、Sewing time:2.5 sec/pcs、Output:10 sec/pcs	