



SIRUBA

銀箭牌

BT430Q-08A

Electronic Radial-tacking Machine with Hole-Punch

电子冲孔帽眼机



应用范围

APPLICATIONS

适用于箱包、帽类、服饰类等产品的冲孔、绣眼工艺。

Punching and radial-tacking function suitable for products such as bags, hats, and clothing.




特点

FEATURES

无油机构设计：
采用DLC 针棒，挑线机构轴承设计，以
固态油脂润滑，有效防止面料油污问题。

Oil-free Mechanism Design:
With DLC needle bar, thread take-up
lever's bearing design, and grease
lubrication, it avoids the problem of
oil stain.



操作面板内建USB埠：
以USB 记忆体进行图形资
料储存，方便快捷。

Control Panel with Built-
in USB port:
It is easy and convenient
for Pattern input by USB
memory.



1 冲孔、绣眼两道工艺一次完成，孔位精准，线迹美观。

标配可编程的大尺寸彩色触控屏，花样程式可轻松
编辑与设置，简单便捷。

冲头外径可选配，冲头压力可依要求调整。

Punching and radial-tacking in one step, with precise
hole positioning and beautiful stitching. Equipped
with a programmable large-sized color touchscreen
as standard, pattern programs can be easily edited
and set up, making it simple and convenient. Punch
head diameter and pressure can be selected and
adjusted as required.

2 适用范围大：

中厚料规格，可以改进挑线行程，提高线迹稳定度，扩大厚料缝制性能。

Wider Range of Sewing Application :

For heavy material, with thread take-up lever's stroke changing, it
makes the stitches stable and upgrades the sewing performance.

3 短线头设计：

改进切线结构，在针孔最近点线，使线长度变短，减少修线工作。

Short Thread End Design :

Improving the thread trimming mechanism to cut the thread at the
nearest spot from the needle. It shortens the thread end and reduces
the finishing job.



规格

SPECIFICATIONS

型号 Model	BT430Q-08A						
用途 Application	01 标准 Standard	02 厚料 Heavy material	03 帽眼 Radial tacking	05 裤耳 Belt loop	06 松紧带拼接 Elastic Band Joining	07 针织 Knits material	08 冲孔、绣眼 Punching and radial-tacking
最高缝制速度 Max. Sewing Speed	3200 S.P.M.						
缝制区域 (X x Y) Sewing area (X x Y)	40X30	40X30	15X15	40X30	9X40	40X30	15X15 冲孔Hole size: Ø 3mm
送布方式 Feeding	间歇性送布 (步进马达驱动) · Intermittent Feeding (Stepping motor drive mode)						
针距 Stitch length	0.05~12.7 mm						
最大针数 Max. stitch	5000 针/ 图形 · 5000 stitch / pattern						
抬压脚 Presser foot lifter	步进马达驱动 · Stepping motor drives						
压脚 / 钮夹上升量 Height of Presser foot/ Button clamp Lifting	Max. 17mm						
旋梭 Hook	半旋转标准旋梭 · Standard Shuttle hook						
外部资料储存 External Data storage	经由 USB 埠 · Inputted by USB Port						
循环缝 Cycle program	最多30 组, 每组上限50个步骤 · Max. 30 sets, each set includes Max. 50 steps.						
记忆容量 Memory Capacity	内建 89种图形 · Built-in 89 patterns 最多可追加 799种图形 / 500,000 针 · Max. 799 patterns / Max. 500,000 stitches can be added						
马达 Motor	直驱式 AC伺服马达 550W · Direct-drive AC Servo Motor 550W						
电源 Power	单相 220V · Single Phase 220V						
重量 Weight	机头: 约 57 kg, 操作面板: 约 0.4 kg, 控制箱: 约 9 kg · Machine Head: about 57 kg, Operation Panel: about 0.4 kg, Contro Box: about 9 kg						



高林股份有限公司
KAULIN MFG. CO., LTD.

由於对产品的改良及更新，本产品型录中之产品规格及外观的修改恕不事先通知！
The specification and/or appearances of the equipment described in this catalogue
are subject to change without previous notice because of modification.

C.S2023-21. MAY. 2024