



# D007L/ET/EK/EW7

四針六線並縫機搭配電動切線及  
抬壓腳裝置

Four-Needle Six-Thread Flatseam  
Machine with Electric Thread Trimmer  
and Presser Foot Lifter

## 特點

## FEATURES



線道採精密陶瓷設計，使過線收線更加順暢，線跡更均勻穩定，有效提升車縫效果。

The ceramic precision design of the line that makes the winding line is smooth. Stitches are better stable and average, and the sewing effect is effectively improved.



抬壓腳機構彈性伸縮防塵保護套：有效防止布屑及灰塵進入。

Presser foot lifting mechanism with a flexible dust-proof protective cover: effectively prevents fabric scraps and dust from entering.



前後機體包覆式設計，可防漏油、灰塵。

The front and rear body fully enclosed design to prevent oil leaks and dust ingress.




馬達加裝散熱風扇，高速車縫較穩定。

Motor equipped with a cooling fan for more stable high-speed sewing.



一體成型擋油牆：有效防止漏油可能。  
Integrated oil retaining wall: effectively prevents potential oil leaks.



外撥式針距調整撥桿設計，可輕易滿足各種布類針距需求。

External dial-type stitch length adjustment design allows easy setting to meet various fabric requirements.

## 配件 DEVICE

**EK** 電眼電動切線組  
Sensor controlled electronic type chain cutter

**EW7** 電動式吸布屑組 ( 搭配 EK )  
Electronic type waste suction set (for EK)

**AK** 電眼氣動切線組  
Sensor controlled pneumatic type chain cutter

**AW7** 外接空壓式吸布屑組 \* 需外接空壓機 ( 搭配 AK )  
External compressor type waste suction set  
\*for compressor compatible (for AK)

**1** 有效取代傳統手工剪線流程，省時、省力、提高生產效率。  
Effectively replaces traditional manual thread trimming, saving time and effort while improving production efficiency.

**2** 使用氣動 / 電動驅動吸線頭更穩定、確實，特別適用於薄布料。  
The use of pneumatic/electric drive to remove thread ends is more stable and reliable, especially suitable for thin fabrics.

**3** 滑軌設計較耐久使用，無須擔心鬆線問題。  
The slide rail design is durable, therefore eliminating concerns about loose threads.

**4** 獨特刀架設計調節方便，精準剪線穩定。  
The unique knife holder design is easy to adjust and provides precise and stable cutting.

**5** 光眼布邊識別，專業反光面設計杜絕識別失誤更加穩定。  
Eye-sensor fabric edge detection with a specialized reflective surface design ensures more stable recognition and eliminates errors.

**6** 多項可調式功能設計，包含斬刀滑軌、吸風裝置、線頭吸風高度與活動刀壓力皆可依需求靈活調整，差動調整更直覺，輕鬆因應各類布料，實現最佳縫製品質。  
Multiple adjustable functions, including the cutter with slide rail, suction device, thread suction height and movable knife pressure, can be flexibly adjusted according to needs. Differential adjustment is more intuitive, easily adapting to various fabrics and achieving optimal sewing quality.



# 規格

# SPECIFICATIONS

## 1 2 3 4 5 7 8 8

# D007L - 4 52 - 02 H - ET/ EK /EW7

- 1** 機種別  
Model
- 2** 針數  
Needle Numbers
- 3** 針距  
Needle gauge
- 4** 單 / 雙切刀  
Single/Double Trimmer
- 5** 特殊規格  
Special Specification
- 6** 車縫功能  
Seaming Function
- 7** 抬壓腳規格  
Foot Lifter Specification
- 8** 配件  
Device

D007L									
D007L-452-01	4	6	5.2	1.6   2.5	1 : 0.7   1 : 1.5	8	6	FL X 118GCS (4 PCS)	4200
D007L-460-01			6.0						
D007L-452-02			5.2						
D007L-460-02			6.0						
D007L-452-02R			5.2						
D007L-460-02R			6.0						
D007L-452-02H			5.2						
D007L-460-02H			6.0						
D007L-452-02H1			5.2						
D007L-460-02H1			6.0						

**Remarks :**

FLG - 1 為假針規格·避免車縫薄軟面料之縫份起皺·

FLG - 1 is a retainer for seaming light / soft materials without seam wrinkling.

1 Model	4 Trimming	Cross-section	Fabric Weight		
			Light	Medium	Heavy
D007L-452-01					
D007L-460-01					
D007L-452-02					
D007L-460-02					
D007L-452-02R					
D007L-460-02R					
D007L-452-02H					
D007L-460-02H					
D007L-452-02H1					
D007L-460-02H1					



由於對產品的改良及更新·本產品型錄中之產品規格及外觀的修改恕不事先通知  
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

MAY. 2026