

S007KD SERIES FEATURES



自動切線系列新設計上夾線裝置，出刀迅速精準，夾線穩定

Auto trimmer with newly designed upper thread gripper, trims precisely and stably.



PCH-3M [三合一] 一般平縫 / 下擺車縫 / 拷克倒骨蓋縫

三合一 平縫，倒骨，折下擺，更換作業組裝方便，多樣化功能，提供生產廠商高效率低成本。

PCH-3M (3 in 1): GENERAL SEAMING/BOTTOM HEMMING/COVERING STITCH (Fold-down type)
3-in-1 model for multifunctional and efficient production with lower cost.



超小筒徑圓周只有180毫米，車縫小孔徑圓筒針織物，更加方便就手

The small cylinder designed with 180 mm, the extremely small circumference makes sewing operation smoother.



外置式底線分線盤，置於機體前方，調整容易，拆裝方便，可輕易清除絞線

Front exposed looper thread take-up mechanism makes cleaning and adjusting more convenient. After fine tuning the looper thread eyelet holder, sewing can be more accurate.



調整式進布誘導器，活動式壓腳，車縫適用性更廣

Adjustable folder, flexible presser foot, able to accomodate wider range of sewing items.



超短筒的設計，筒邊至中針距離只有39毫米，採密封式之側蓋設計，操作方便順暢

Extremely small tubule design, the distance from cylinder edge to middle needle is only 31 mm. Sealed side cover makes operation more convenient.




密縫裝置

藉由縮短送具行程，在車縫起始或結束進行密縫的功能，確保縫線不易脫落,提高車縫品質，基本車為腳踏板控制，電動和氣動控制為選配。

Condense Stitching Device

By reducing the strokes of feed dog, at the beginning and the end of sewing, condense stitching reinforces the stitches. This enhances the sewing sturdiness and quality. Basic model is controlled by pedal. Electric and pneumatic controls are optional.



自動切線系列新設計氣/電動上下切刀組，出刀迅速穩定精準，切線俐落，輕順低噪音調整容易

Auto trimmer with newly designed pneumatic / electric trimming system, trims precisely and stably, reduce sound and easy to adjust.



全新設計之內藏式定位器，定位精準，徹底解決外置式定位器，不易安裝，調整及定位不穩之情形

Newly designed built-in synchronizer, makes position precisely and stably, easy to adjust.



圓形粗細針縫目調整鈕的設計，隨心所欲精確調整縫目長短

Circular stitch length adjustment button, easily to adjust stitch length.



小型投射LED照明，穿線或調整機針作業方便（選配）

LED light, convenient for threading or adjusting the needle (Optional).

規格

SPECIFICATIONS

S007KD - W122 - 2 40/ PCH-3M/ DSKU

規格索引，詳細請參考P.71 Specification index, please refer to P.71

① 機種別 Model

④ 功能 Function

⑦ 針距 Needle gauge

⑨ 馬達 Motor

② 系列 Series

⑤ 針板舌片 Needle Plate Finger

⑧ 配件 Device

U : U Series

H : H Series

③ 網線方式 Covering Types

⑥ 針數 Needle Numbers

S1



S007KD-W122-⑥⑦/PCH-3M/(⑨)

2

4

4.0/ 4.8

1.4 ~ 4.2

0.8 ~ 1.4

5/7

H / U

4000

3

5

5.6/ 6.4

1.4 ~ 4.2

0.8 ~ 1.4

5/7

H / U


4000

**PCH-3M [三合一] 一般平縫／下擺車縫／拷克倒骨蓋縫**

三合一 平縫，折下擺，倒骨，更換作業組裝方便，多樣化功能，提供生產廠商高效率低成本。

**PCH-3M [3 IN 1] :
GENERAL SEAMING/BOTTOM HEMMING/COVERING
STITCH (Fold-down type)**

3-in-1 model for multifunctional and efficient production with lower cost.



選購配件 OPTIONAL DEVICE

UTT, UTU, UTX, UTY, CMR, SAR/UTT, SAR/UTU

S2



S007KD-W322-⑥⑦/PCE/(⑨)

2

4

4.0/ 4.8

1.4 ~ 4.2

0.8 ~ 1.4

5/7

H / U

4000

3

5

5.6/ 6.4


1.4 ~ 4.2

0.8 ~ 1.4

5/7

H / U

4000

**拷克立骨蓋縫**

適宜中厚布料，經三線拷克車縫後再包縫，用於運動服、汗衫等領口、下擺、袖管等之拷邊車縫後加以包縫，可增加服飾之美觀及車縫之牢固，利用導布片及壓具上之壓刀導縫，可避免車縫時彎曲不直。

OVERLOCK-SEAM COVERING (Flatting Type)

Bulging seam covering for medium fabric after 3 thread plain seaming, suitable for neck openings, sleeve, cuff or bottom of sportswears, T-shirts, etc... With fabric guide and special presser foot, making sewing easy and more efficient.

選購配件 OPTIONAL DEVICE

UTT, UTU, UTX, UTY, SAR/UTT, SAR/UTU, CMR

規格

SPECIFICATIONS

S007KD - W121 - 2 40 /FFT/DSKU

規格索引，詳細請參考P.71 Specification index, please refer to P.71

- | | | | |
|-----------------------|----------------------------|-------------------|--------------|
| ① 機種別 Model | ④ 功能 Function | ⑦ 針距 Needle gauge | ⑨ 馬達 Motor |
| ② 系列 Series | ⑤ 針板舌片 Needle Plate Finger | ⑧ 配件 Device | U : U Series |
| ③ 網線方式 Covering Types | ⑥ 針數 Needle Numbers | | H : H Series |

S3

	⑥		⑦					⑨	
S007KD-W121-⑥⑦/FFT/⑨	2	4	4.0/4.8	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
	3	5	5.6/6.4	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
S007KD-W122-⑥⑦/FFT/⑨	2	4	4.0/4.8	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
	3	5	5.6/6.4	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
S007KD-W131-⑥⑦/FFT/⑨	2	4	4.0/4.8	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
	3	5	5.6/6.4	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
S007KD-W132-⑥⑦/FFT/⑨	2	4	4.0/4.8	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000
	3	5	5.6/6.4	1.4 ~ 4.2	0.8 ~ 1.4	1~5.5	5	H / U	4000



FFT 上送布功能

專利優化前後移動送具之結構設計，有效送布行程大，車縫送布更穩定。


FFT TOP FEEDING FUNCTION

Back and forth moving feed dog is designed by patent and improved mechanism. The effective feeding stroke is bigger, and fabric feeding is more stable.


選購配件 OPTIONAL DEVICE

UTT , UTX


X Brand



Y Brand



SiRUBA



規格 SPECIFICATIONS S007KD-U173-1 00/ SAR/ RF/ UTT/ DSKU

規格索引，詳細請參考P.71 Specification index, please refer to P.71

- | | | | |
|-----------------------|----------------------------|-------------------|--------------------------------|
| ① 機種別 Model | ④ 功能 Function | ⑦ 針距 Needle gauge | ⑨ 馬達 Motor |
| ② 系列 Series | ⑤ 針板舌片 Needle Plate Finger | ⑧ 配件 Device | U : U Series |
| ③ 網線方式 Covering Types | ⑥ 針數 Needle Numbers | | H : H Series |
| | | | *UTT 請參考 Please refer to P.121 |

S4



S007KD-U173-100/SAR/RF/UTT/⑨	1	2	-	1.4 ~ 4.2	0.8 ~ 1.4	5/7	H / U	4000
------------------------------	---	---	---	-----------	-----------	-----	-------	------



S007KD-U173-100/SAR/RF/UTT/⑨

單針鏈縫牛仔褲轆腳機

針對彈性牛仔布料的車縫所開發的規格，配備專用的氣動式轆腳喇叭，因為具有差動送布功能，可以車縫出美觀平整的效果。

標配：氣動式自動切線
氣動抬壓腳
直驅伺服馬達
結束密縫

SINGLE NEEDLE CHAINSTITCH JEANS BOTTOM HEMMING MACHINE

Special gauge for elastic denim fabric, and equipped with pneumatic hemming folder. Because of the function of differential feeding, the sewing quality is nice and perfectly flat.

Standard Equipment: Pneumatic thread trimmer
Pneumatic presser foot lifter
Direct drive servo motor
Condensed stitching device



S5



S007KD-W812-2 ⑦/SRL/UTT/⑨	2	5	4.0/ 4.8	1.4 ~ 4.2	0.8 ~ 1.4	5/7	H / U	4000
S007KD-W812A-2 ⑦/SRL/UTT/⑨	2	5	4.0/ 4.8	1.4 ~ 4.2	0.8 ~ 1.4	5/7	H / U	4000
S007KD-W812A-3 ⑦/SRL/UTT/⑨	3	5	5.6/ 6.4	1.4 ~ 4.2	0.8 ~ 1.4	5/7	H / U	4000



S007KD-W812A-356/SRL/UTT/⑨

左切刀下擺車縫

左切刀修布邊/下擺車縫工程適用於小筒型繃縫車。

BOTTOM HEMMING WITH LEFT SIDE FABRIC TRIMMER

Left edge trimmer designed for small cylinder machine with auto thread trimmer function.

