



ASL-SVS100

自動邊叉機

Automatic Side Slit Sewing Machine



特點

FEATURES

- 1 **壓腳專利技術：機械式同步結構，確保在高速縫紉時，上下層布料不會產生位移或產生皺摺。**
Patented Synchronous Presser Foot: Prevents fabric shifting or puckering during high-speed sewing.
- 2 **垂直下壓壓板：針對不同厚度的開叉處提供均勻壓力，解決了傳統側面受力不均導致的縫線歪斜問題。**
Vertical Pressure Plate: Delivers uniform pressure for consistent, straight seams across various fabric thicknesses.



三尖叉
Triangle Side Vent



車縫連套結
Side Vent with Bartack



原身叉
Side Vent



捆條叉
Side Vent with Tape

- 3 **人體工學設計：升降式儲存槽讓更換下線（梭心）與取料更輕鬆，減少重複彎腰動作，大幅節省停機時間。**
Ergonomic Design: Elevating storage system for quick bobbin changes and easy material handling, significantly reducing downtime.
- 4 **內建 1500W 高功率真空馬達，產生的吸力能將布料牢牢固定在模板上。**
1500W High-Power Suction: Securely holds fabric on the template, eliminating the need for pre-ironing.
- 5 **吸風力大小可根據布料厚度（針織或梭織）自由調整，確保輕薄布料不移位、厚重布料吸得住。**
Adjustable Suction Control: Tailored for both knits and wovens to ensure stable positioning regardless of fabric weight.
- 6 **自動偵測告警：標配智能斷線感測，斷線立即停機報警，減少不良品產出。**
Smart Thread Breakage Detection: Features real-time sensors with auto-stop and alarms to minimize waste.



規格

SPECIFICATIONS

型號 Model	ASL-SVS100			
縫紉機機頭 Machine Head	SiRUBA DL8000P-BM1L-16Q			
車縫範圍 Sewing Range	模具 Mold	12cm x 6cm	氣壓 / 耗氣量 Air Pressure / Air Consumption	0.5 Mpa / 4L
	車縫 Sewing	30cm x 29cm		
車縫速度 Sewing Speed	2500 SPM (Max)		產能 Capacity	180 件 / 小時 180 PCS / Hour



由於對產品的改良及更新，本產品型錄中之產品規格及外觀的修改恕不事先通知！
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.