

## DT8600

Big Hook Double-Needle Lockstitch Machine  
with Thread Trimmer

機電一體 大梭切線雙針車



youtube



- 上軸採用通軸設計，整體力矩輕，機器運轉平穩，送料流暢。
- 採用750W大功率伺服電機直接驅動，噪音低、振動小、安裝方便、啟動停車反應迅速，機針貫穿力強。
- 全自動切線、掃線、倒縫、抬壓腳裝置，操作簡便迅速。(功能款/C)

- The upper shaft adopts the through-all design; the overall torque is light; the machine runs smoothly; and the feeding is smooth.
- 750W high-power servo motor: larger needle penetration force, lower noisy, lower vibration, easier to install and shorter responding time.
- Fully automatic thread trimming, thread releasing, thread sweeping, reverse stitching, and presser foot lifting mechanisms enable quick and easy operation.

# 特點

# FEATURES

**1** 縫距控制鈕：轉動調整達到理想縫距。  
Stitch length control button : Rotate to get ideal stitch length.

**2** 邊角縫裝置：從縫紉角度和針數決定距寬，來做到美麗之邊縫。  
Split stitching device : Decide the ideal width by sewing angle and stitches numbers, it will make good quality of split stitching.

**3** 倒縫撥桿裝置：可以輕鬆實現倒縫縫紉。  
Reverse lever : Easy to achieve reverse seam.

### 功能款 / C 附加自動化配置

**C-1** 直刀剪線結構：直刀剪線機構，剪線穩定。  
Straight knife system : Straight knife thread trimming mechanism, stable thread trimming.



# 規格

# SPECIFICATIONS

DT8600	mm	Needle No. DP×5	布料厚度 Fabric Weight			mm 手動 Hand	mm	S.P.M. (Max)	mm	KG
			L	M	H					
42	4.8 / 6.4	#14 - #22				7	M : 0~4 H : 0~5	3600	L740 W330 H663	49 / 52
45								3000		
72							M : 0~7 H : 0~7	3000		
75										

功能 Function	規格 Sub-Class	針送 Needle Feed	標準旋梭 Standard Hook	大旋梭 Big Hook	角縫 Split Needle Bar
		42	V	V	-
	45	V	V	-	V
	72	V	-	V	-
	75	V	-	V	V

\*功能款 / C 附加多項自動化配置：①自動切線 ②快速倒縫 ③自動抬壓腳 ④撥線桿

\*Option C Equipped With Additional Functions: ①Auto Trimming ②Reverse Feeding ③Auto Lifter ④ Wiper



高林股份有限公司  
KAULIN MFG. CO., LTD.

由於對產品的改良及更新，本產品型錄中之產品規格及外觀的修改恕不事先通知！  
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

AUG. 2025