



HDS-269D

高效能圓筒型綜合送布平縫機

High-performance cylinder bed
compound feed machine

特點

FEATURES

適用於厚料與立體縫製(包袋、包包等縫)。

Suitable for heavy materials and 3D sewing applications such as bags and luggage.



直驅馬達：低噪音、高效率、節能運行。

Large Capacity Hook System: Reduces bobbin change frequency for higher productivity.



大直徑圓筒縫台：直徑 76mm，適用立體與筒狀產品縫製。

Stepping motor for thread trimming and foot lifter, more quiet, quickly response, more durable.

HDS-269D-273

1 採用 2.5 倍大旋梭：減少更換梭芯與線軸次數，提高作業效率。

Large Capacity Hook System: Reduces bobbin change frequency for higher productivity.

2 273 針距：預設 6 mm，另提供 8/10/12 mm 可選。

273 Needle Gauge :
Standard 6 mm, optional 8 / 10 / 12 mm

代碼 Function Code	單針 Single Needle	雙針 Double Needle
HDS-269D-373	標準線跡長度 6 mm Standard stitch length 6 mm	-
HDS-269D-273	-	標準線跡長度 8 mm Standard stitch length 8 mm



RAP 氣動倒回縫+氣動抬壓腳

氣壓自動壓腳提升裝置、氣壓自動反向縫合裝置,提升操作便利與效率。

RAP Pneumatic Reverse Stitching + Presser Foot Lift

Back and forth moving feed dog is designed by patent and improved mechanism. The effective feeding stroke is bigger, and fabric feeding is more stable.

規格

SPECIFICATIONS

HDS-	x	Needle No.	mm	mm		mm	KG	S.P.M. (Max)	mm	
				手動 Hand	膝動 Knee					
HDS-269D-373	1	2	134-35 110-140	-	6	10	6	37/48	2000	L700 W330 H720
HDS-269D-273	2	4	134-35 110-140	4.8-24	6	10	6	37/48	2000	

選購配件 OPTIONAL DEVICE : RAP



高林股份有限公司
KAULIN MFG. CO., LTD.

由於對產品的改良及更新，本產品型錄中之產品規格及外觀的修改恕不事先通知！
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

MAR. 2026