

# SIRUBA®

銀箭牌工業用縫紉機

INDUSTRIAL SEWING MACHINE



## P700K & R700K SERIES

单/双 针高头车 · 单/双 针罗拉车  
One / two needle post-bed lockstitch machine



用於运动休闲鞋，皮鞋、皮件及帽子等圆弧或窄面之缝制。  
Sewing narrow and curved areas for shoes, sport shoes, leather goods and caps...etc.

**R**

机种别  
Machine Type

P: 高头车  
Post-bed lockstitch machine

R: 罗拉车  
(底部轮型送具及轮型驱动押具)  
Post-bed lockstitch machine  
(With wheel feed and driven roller  
presser)

**7 2 8 K**

针数  
Needle Numbers

1: 单针  
1-Needle

2: 双针  
2-Needle

针距规格  
Needle gauge specification

Model	Specification	Needle Gauge	Function
P717K	<b>01</b>	-	Bottom feed
P727K	<b>12</b>	1.2 mm	Bottom feed
	<b>16</b>	1.6 mm	Bottom feed
	<b>24</b>	2.4 mm	Bottom feed
R718K	<b>01</b>	-	Bottom feed
	<b>02</b>	-	Needle feed
R728K	<b>16</b>	1.6 mm	Bottom feed
	<b>20</b>	2.0 mm	Bottom feed
	<b>24</b>	2.4 mm	Bottom feed
	<b>224</b>	2.4 mm	Needle feed

**2 2 4**

轮钱组规格  
Driven roller presser

-: 中轮钱  
Middle roller presser

H: 粗线用中轮钱  
Middle roller presser for thick thread

**H**



### 特点

- \* 切刀机构易于安装，调整，且结构坚固，用于切断细线与粗线，皆可获得高品质的切线效果。
- \* 切线时，电磁阀采用独立系统，能确实控制过线组的松线动作，使切线效果更完善。
- \* 相关延伸机种，附气动式自动提升轮钱装置，操作简易，增进缝制效率。

### CHARACTERISTICS

- \* The trimmer is strong , easy to be installed and adjusted. It is good at cutting any specification of thread.
- \* The solenoid is an independent system, which can firmly control the action of thread take up, and makes the trimmer work perfectly.
- \* The optional equipment is with pneumatic auto lifter for driven roller presser. It is efficient and easy to handle.

### R700K 系列



• R718K



• R728K

### R700K

单/双 针罗拉车(底部轮型送具及轮型驱动押具)  
One / two needle post-bed lockstitch machine  
(With wheel feed and driven roller presser)

机型 MODEL	功能 Function	X 针数 Number of Needle	针距(mm) Needle Gauge		缝距(mm) Stitch Length	押具扬程(mm) Presser Foot Lift		针 Needle No.	S.P.M 车缝速度
			○	○○		手动Hand	膝动Knee		
R718K-01	Bottom feed	1	-	-	0-4.5	7	12	DPX5 #16	2500
R718K-01H	Bottom feed	1	-	-	0-4.5	7	15	DPX17 #23	2500
R718K-02	Needle feed	1	-	-	0-7	7	12	DPX5 #16	2500
R718K-02H	Needle feed	1	-	-	0-7	7	15	DPX17 #23	2500
R728K-16	Bottom feed	2	1.6	-	0-4.5	7	12	DPX5 #16	2500
R728K-20	Bottom feed	2	2.0	-	0-4.5	7	12	DPX5 #16	2500
R728K-24	Bottom feed	2	2.4	-	0-4.5	7	12	DPX5 #16	2500
R728K-24H	Bottom feed	2	2.4	-	0-4.5	7	15	DPX17 #23	2500
R728K-224	Needle feed	2	2.4	-	0-7	7	12	DPX5 #16	2500



## P700K & R700K SERIES

单/双 针高头车 · 单/双 针罗拉车  
One / two needle post-bed lockstitch machine

### P700K 系列



• P717K



• P727K

### P700K

单/双 针高头车  
One / two needle post-bed lockstitch machine

机型 MODEL	针数 X Number of Needle	针距(mm) Needle Gauge		缝距(mm) Stitch Length mm	押具样式 Presser foot type	押具扬程(mm) Presser Foot Lift		针 Needle No. Needle	S.P.M 车缝速度
		○	○○			手动Hand	膝动Knee		
P717K-01	1	-	-	0-4		7.2	10	DPX5 #16	3000
P727K-12	2	1.2	-	0-4		7.2	10	DPX5 #16	3000
P727K-16	2	1.6	-	0-4		7.2	10	DPX5 #16	3000
P727K-24	2	2.4	-	0-4		7.2	10	DPX5 #16	3000

功能 Function : 下送布 Bottom Feed

高林股份有限公司  
KAULIN MFG. CO., LTD.

由於对产品的改良及更新，本产品型录中之产品规格及外观的修改恕不事先通知！

The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

TOP 100  
TAIWAN BRANDS

GOOD DESIGN

CE

ISO 9001:2000

ISO 9001:2000  
ISO 14001:2004

CAT.S2012-35.12

